

# ALPINE ATF DEXRON III

## Description

ALPINE ATF DEXRON III is a versatile ATF, which meets the requirements of the General Motors DEXRON III H specification.

## Field of application

ALPINE ATF DEXRON III can be used in hydraulic systems, hydrostatic drives and also automatic transmissions, where this is specified by the manufacturer.

## Advantages

- Very good low-temperature performance
- High temperature stability
- Excellent ageing properties
- Provides excellent protection against wear and corrosion
- Early identification of leaks thanks to the red colour

## Specifications

DEXRON III H

Safety + Performance

DEXRON III G, DEXRON IID; TYPE A; SUFFIX A; ZF TE-ML 03D, 09, 17C; ALLISON C-4; CAT TO-2

## Technical data

Properties	Unit	Test according to	Values
Colour		DIN ISO 2049	red
Density at 20 °C	g/ml	ASTM D 4052	0.857
Viscosity at -20 °C	mm <sup>2</sup> /s	DIN 51562-1	1070
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	35.9
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	7.4
Viscosity index		DIN ISO 2909	179
Brookfield -40°C	mPa·s	ASTM D 2983	18900
Pourpoint	°C	ASTM D 5950	-51
Flash point	°C	DIN EN ISO 2592	>200

Water hazard class: WGK 1

Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.