



ASPEN 2T / 4T

Alkylate petrol

Description

MOTOREX ASPEN is a clean, environmentally friendly alkylate petrol. This petrol for equipment is derived from refinery gases processed to make an exceptionally pure fuel.

ASPEN 2T is blended with 2% fully synthetic, biodegradable two-stroke engine oil.

Advantages

- Develops substantially fewer unpleasant and dangerous petrol vapours and emissions
- Better performance and lower consumption
- Increases the service life of engines
- Fewer deposits

Field of application

ASPEN 2T is suitable for power saws, clearing saws, hedge trimmers, leaf blowers and other air-cooled two-stroke engines.

ASPEN 4T is suitable for lawn mowers, ride-on tractor lawn mowers, snow-clearing equipment and other machines with four-stroke engines.

Specifications ASPEN 2T

SN 181163:2015, JASO FB

Specifications ASPEN 4T

SN 181163:2015

Technical data alkylate petrol

Properties	Unit	Values 2T	Values 4T
Octane number	RON	95	95
Octane number	MON	92	92
Density at 15 °C	kg / m ³	697.5	691.1
Vapour pressure	kPa	55-65	55-65
Lead content	mg / l	< 2	< 2
Sulphur	ppm	1	1
Aromatic content	Vol-%	< 0.1	< 0.1
Benzol content	Vol-%	< 0.01	< 0.01

ASPEN 2T Water hazard class: WGK 2

ASPEN 4T Water hazard class: WGK 3

Disposal code: EWC 130 702

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.



MOTOREX AG LANGENTHAL

Industrie-Schmiertechnik
 Postfach, CH-4901 Langenthal, Schweiz
 Tel. +41 (0)62 919 74 74, Fax +41 (0)62 919 76 96
www.motorex.com

BUCHER AG LANGENTHAL

MOTOREX-Schmiertechnik
 Postfach, CH-4901 Langenthal, Schweiz
 Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95
www.motorex.com