



# ATF SUPER

Automatic Transmission Fluid

## Description

MOTOREX ATF SUPER is a versatile ATF fluid for use in older vehicles. The base oils selected for this application and the specially formulated additives ensure that the product has optimum lubricating properties, which allow good and reliable performance.

## Field of application

MOTOREX ATF SUPER is recommended for ATF applications with stipulated specifications.

## Advantages

- Provides excellent protection against wear and corrosion
- High shear stability
- Good anti ageing properties
- Facile gear-changing characteristics
- Especially for older vehicles

## Specifications

DEXRON II D; MERCON; MB-Approval 236.6; ZF TE-ML-04D, 05L, 09, 11A, 14A, 21L; VOITH 55.6335; TASA; CAT TO-2; ALLISON C-4

## Safety & Performance

MAN 339 Typ V1/Z1; VOLVO 97335; ZF TE-ML-17C

## Technical data

Properties	Unit	Test according to	Values
Colour		DIN ISO 2049	red
Density at 20 °C	g/ml	ASTM D 4052	0.866
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	38.9
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	7.6
Viscosity index		DIN ISO 2909	168
Brookfield -40°C	mPa·s	ASTM D 2983	47000
Pourpoint	°C	ASTM D 5950	-45
Flash point	°C	DIN EN ISO 2592	>200

Water hazard class: WGK 1  
Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.

