



ATV QUAD RACING 4T

SAE 10W/50

Fully synthetic high-performance engine oil for 4-stroke ATV/Quads

Description

MOTOREX ATV QUAD RACING 4T is a fully synthetic high-performance engine oil, especially manufactured for sporty ATV/quads. This oil provides the engine with optimum protection, even for the toughest requirements in the field of all-terrain vehicles (ATV). JASO MA approval ensures that the oil will work perfectly with wet multi-disc clutches.

Advantages

- Fully synthetic
- Specially developed for sporty ATVs/quads
- Optimum engine protection in all operating areas
- Extremely good thermal stability
- Catalytic converter tested
- Ideal for wet multi-disc clutches (JASO MA approval)

Field of application

MOTOREX ATV QUAD RACING 4T SAE 10W/50 has been developed for the high demands in sporty ATVs/quads with powerful engines. Ideal for ATVs/quads with wet multi-disc clutches. Also meets the highest manufacturer's specifications.

Specifications

JASO MA
API SL, SJ, SH, SG



JASO T 806: 2006
PERFORMANCE IS GUARANTEED by
BUCHER AG

Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 300	10W/50
Colour		DIN ISO 2049	brown
Density at 20 °C	g/ml	ASTM D 4052	0.860
Viscosity at 40 °C	mm ² /s	DIN 51562-1	114.8
Viscosity at 100 °C	mm ² /s	DIN 51562-1	17.5
Viscosity according to HTSH at 150 °C	mPa·s	CEC-L-36-A-97	≥ 3.5
CCS at -25 °C	mPa·s	ASTM D 5293	4550
Viscosity index		DIN ISO 2909	168
Pourpoint	°C	ASTM D 5950	- 48
Flash point	°C	DIN EN ISO 2592	>200
NOACK	% by weight	CEC-L-40-A-93	5.1

Water hazard class: WGK 1
Disposal code: EWC 130 206

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.

