

EXTRA

SAE 20W/20

Monograde motor oil

Description

MOTOR OIL EXTRA SAE 20W/20 is a monograde motor oils for petrol and diesel engines that are used at constant temperatures. Based on select mineral oils and coordinated additives, the formula offers a good level of protection against wear and ensures a long engine service life.

Advantages

- especially for engines at a constant operating temperature
- wide range of applications
- low sulphate ash content
- low oil consumption
- no shearing waste

Field of application

MOTOR OIL EXTRA SAE 20W/20 is suitable for vehicles, motorbikes and stationary systems that are operated with monograde motor oils. EXTRA monograde oils can also be used in specific gears and hydraulic systems for which monograde motor oils are required.

Notes

Please observe the manufacturer's instructions.

Specifications

API SF; API CF; API CD

Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm ³	ASTM D4052	0.883
Viscosity at 40 °C	mm ² /s	DIN 51562-1	52.1
Viscosity at 100 °C	mm ² /s	DIN 51562-1	7.6
Viscosity index		DIN ISO 2909	110
Pourpoint	°C	ASTM D5950	-27
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-15 / 2290
Sulphate residue content	%	DIN EN ISO 6245	1.2
TBN	mg KOH/g	DIN ISO 3771	7.6

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.