

FOREST & GARDEN FS 2T

Fully synthetic two-stroke engine oil

Description

FOREST & GARDEN FS 2T is a fully synthetic two-stroke engine oil. This high-performance product is manufactured from first-class base oils and additives especially formulated for hard use in two-stroke forest-ry, garden and small tools that become hot during operation and are frequently started cold.

Advantages

- Fully synthetic
- Low-smoke
- Suitable for two-stroke engines that become hot during operation
- Reduces combustion residues
- Ideal for injection engines
- Low-ash combustion
- Tested for use with catalytic converters
- Enhanced corrosion protection

Field of application

FOREST & GARDEN FS 2T is specially formulated for use in two-stroke engines that become very hot during operation, as is the case for chainsaws, lawnmowers, trimmers, hedge trimmers and other tools. It is generally suitable for two-stroke engines that operate at high temperatures with high outputs for "stop and go" use or continuous operation.

Specifications

API TC; JASO FD; ISO-L-EGD

Notes

Suitable for both injection and pre-mix lubrication. A mixing ratio of 1:50 is usually adequate. Observe the unit manufacturer's instructions.

Technical data

Properties	Unit	Test according to	Values
Colour			red
Density at 20 °C	g/cm ³	ASTM D4052	0.881
Viscosity at 40 °C	mm ² /s	DIN 51562-1	50.1
Viscosity at 100 °C	mm ² /s	DIN 51562-1	9.1
Viscosity index		DIN ISO 2909	164
Pourpoint	°C	ASTM D5950	-40
Flash point C.O.C.	°C	DIN EN ISO 2592	108
Sulphate residue content	%	DIN EN ISO 6245	0.12
TBN	mg KOH/g	DIN ISO 3771	3.0

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

