



# PRISMA HF

## SAE 75W/85

Synthetic performance API GL-4 gear oil.

### Description

MOTOREX GEAR OIL PRISMA HF SAE 75W/85 is a high-lubricity gear oil for synchronised manual gearboxes. Its formulation with special additives produces an oil with an outstanding gear-changing performance, excellent shear and oxidation stability and high protection against corrosion.

### Field of application

MOTOREX GEAR OIL PRISMA HF SAE 75W/85 is an HF high-lubricity gear oil (HF = High Friction) for selected synchronised manual gearboxes in passenger cars and light commercial vehicles.

MOTOREX GEAR OIL PRISMA HF SAE 75W/85 has been tested in different TOYOTA, FORD, MITSUBISHI, SUBARU and DAEWOO gearboxes and has obtained excellent results.

### Advantages

- Synthetic performance
- Good cold starting
- Exact frictional performance
- Optimum wear protection
- Excellent oxidation and shear stability
- Good viscosity-temperature characteristics
- Very low pourpoint

### Specifications

API GL-4

### Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 306	<b>75W/85</b>
Colour		DIN ISO 2049	brown
Density at 20 °C	g/ml	ASTM D 4052	0.856
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	76.8
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	11.5
Brookfield -40 °C	mPa·s	ASTM D 2983	140'500
Viscosity index		DIN ISO 2909	143
Pourpoint	°C	ASTM D 5950	-42
Flash point	°C	DIN EN ISO 2592	> 200

Water hazard class: WGK 2

Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available for the product described.



**BUCHER AG LANGENTHAL**

MOTOREX-Schmiertechnik

Postfach, CH-4901 Langenthal, Switzerland

Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95

[www.motorex.com](http://www.motorex.com)