

PROFILE O-PL

SAE 5W/30

Synthetic performance high-tech motor oil

Description

MOTOREX PROFILE O-PL SAE 5W/30 is a synthetic performance high-tech motor oil. It guarantees optimised lubrication reliability, thanks to the use of state-of-the-art base fluids in combination with perfectly coordinated additives. The pioneering Low-SAPS technology in combination with unique low-friction properties reduces fuel consumption and thus minimises pollutant emissions.

Advantages

- reduces fuel consumption and CO2 emissions
- excellent cold-starting properties
- minimal lubrication time
- optimum protection against wear
- very good low-friction properties
- minimizes effectively the risk of low speed pre ignition (LSPI)
- suitable for CNG, LPG and hybrid vehicles
- Low-SAPS technology

Field of application

MOTOREX PROFILE O-PL SAE 5W/30 is specially developed for vehicles of the GM Group.

Notes

MOTOREX PROFILE O-PL SAE 5W/30 can be mixed with all conventional motor oils of the same performance level. Oil and filters must be replaced in accordance with the manufacturer's specifications.

Specifications

API SN PLUS-RC; ILSAC GF-5; GM DEXOS 1 GEN 2

Safety + Performance

FORD WSS-M2C946-A; FORD WSS-M2C946-B1;
CHRYSLER MS 6395



Technical data

Properties	Unit	Test according to	Values
Colour			yellow brown
Density at 20 °C	g/cm ³	ASTM D4052	0.849
Viscosity at 40 °C		DIN 51562-1	58.2
Viscosity at 100 °C		DIN 51562-1	10.2
Viscosity index		DIN ISO 2909	165
Viscosity according to HTHS at 150 °C		CEC-L-36 A-97	≥2.9
Pourpoint		ASTM D5950	-36
Flash point C.O.C.		DIN EN ISO 2592	≥200
CCS at		ASTM D 5293	-30 / 3800
Sulphate residue content		DIN EN ISO 6245	0.85
NOACK		CEC L-40-A-93	11.3
TBN		DIN ISO 3771	8.5

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

