

# PROFILE V-XL

## SAE 0W/30

Fully synthetic super-low-friction motor oil

### Description

PROFILE V-XL SAE 0W/30 is a synthetic, high-tech motor oil with very good low-friction properties and reduced particle emissions. The latest base fluids combined with special additives guarantee high wear protection and excellent pollutant results.

### Advantages

- Low-SAPS technology
- super-low-friction viscosity
- keeps the engine clean, particularly around the piston rings, thus reducing oil consumption
- stable viscosity-temperature behaviour
- extremely good cold-starting reliability
- quick lubrication rise time
- suitable for CNG, LPG and hybrid vehicles
- reduces CO<sub>2</sub> emissions

### Field of application

PROFILE V-XL SAE 0W/30 is formulated and tested for petrol and diesel engines with exhaust gas after-treatment systems and LongLife service which, in accordance with ACEA, require a C3 with the viscosity SAE 0W/30. Specially developed for vehicles of the Volkswagen Group.

### Notes

PROFILE V-XL SAE 0W/30 can be mixed with all conventional motor oils of the same performance level. Oil and filters must be replaced in accordance with the vehicle manufacturer's specifications.

### Specifications

ACEA C3-16; PORSCHE C30; VW 504 00; VW 507 00

### Technical data

Properties	Unit	Test according to	Values
Colour			light brown
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.844
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	64.0
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	12.2
Viscosity index		DIN ISO 2909	192
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-48
Flash point C.O.C.	°C	DIN EN ISO 2592	≥ 200
CCS at	°C / mPa·s	ASTM D 5293	-35/ 5200
Sulphate residue content	%	DIN EN ISO 6245	0.8
NOACK	%	CEC L-40-A-93	9.2
TBN	mg KOH/g	DIN ISO 3771	8.3

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.