



SELECT LA-X

SAE 5W/30

Synthetic performance high-tech motor oil

Description

MOTOREX SELECT LA-X SAE 5W/30 is a synthetic performance high-tech motor oil based on Mid-SAPS technology. It reduces particle emissions and has very good low-friction properties. The use of state-of-the-art base fluids, in combination with additives developed exclusively for this formula, guarantees optimum lubrication reliability under all usage conditions.

Advantages

- reduces fuel consumption and CO2 emissions
- high cold-starting reliability
- quick lubrication
- excellent shear stability
- optimum protection against wear
- very good low-friction properties
- suitable for CNG, LPG and hybrid vehicles
- Mid-SAPS technology

Field of application

MOTOREX SELECT LA-X SAE 5W/30 is formulated and tested for petrol and diesel engines with exhaust gas aftertreatment systems and LongLife service which, in accordance with ACEA, require a C2 or C3 with the viscosity SAE 5W/30. The lifespan-extending properties for particle filters have been proven in extensive engine tests. Approved by leading vehicle manufacturers.

Notes

MOTOREX SELECT LA-X SAE 5W/30 can be mixed with all conventional motor oils of the same performance level. Oil and filters must be replaced in accordance with the manufacturer's specifications.

Specifications

ACEA C2-16; ACEA C3-16; API SN; BMW Longlife-04; GM DEXOS 2; MB-Approval 229.51; MB-Approval 229.52

Safety + Performance

FIAT 9.55535-S3; MB 229.31; OPEL/VAUXHALL OV0401547; VW 505 00; VW 505 01

Technical data

Properties	Unit	Test according to	Values
Colour			green
Density at 20 °C	g/cm ³	ASTM D4052	0.850
Viscosity at 40 °C	mm ² /s	DIN 51562-1	65.0
Viscosity at 100 °C	mm ² /s	DIN 51562-1	11.4
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-42
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-30 / 6100
Sulphate residue content	%	DIN EN ISO 6245	0.8
NOACK	%	CEC L-40-A-93	10.5
TBN	mg KOH/g	DIN ISO 3771	7.8

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.



BUCHER AG LANGENTHAL

MOTOREX-Schmiertechnik
Postfach, CH-4901 Langenthal, Schweiz
Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95
info@motorex.com, www.motorex.com

MOTOREX AG LANGENTHAL

Industrie-Schmiertechnik
Postfach, CH-4901 Langenthal, Schweiz
Tel. +41 (0)62 919 74 74, Fax +41 (0)62 919 76 96
info@motorex.com, www.motorex.com