

# SPRAY 466

## CORROSION PROTECTION WITH LONG-TERM EFFECT

### Description

Barium-free long-term corrosion protection which after just a short time builds up a tough, non-slip waxy film which protects against external influences. Spray 466 is thixotropic and thus does not run or drip when applied on vertical surfaces. It is ideally suited for the following application areas:

- Preservation (indoor and outdoor storage) of semi-finished and finished products
- Corrosion protection during maritime transport
- Long-term corrosion protection for winter road maintenance vehicles
- Preservation of vehicles and equipment in the construction industry and agriculture during decommissioning
- Underbody protection (classic cars) and cavity protection in the motor vehicle industry

### Advantages

- Excellent long-term corrosion protection
- Simple to apply
- Builds up a non-slip, temperature stable, non-stick wax film
- Heat resistant up to 120°C
- Extremely salt water resistant (ASTM B117 salt spray test > 1000 hours)
- Compatible with all common surface treatments

### Use

Shake well before use. Apply to clean, dry surfaces by spraying from a distance of roughly 20 - 30 cm. Let the wax film dry. SPRAY 466 be easily removed with petroleum spirits or high-pressure cleaners.

### Contents

500 ml



N:VTS/SPRAY 466\_1214



**BUCHER AG LANGENTHAL**  
 MOTOREX-Schmiertechnik  
 Postfach, CH-4901 Langenthal, Schweiz  
 Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95  
[www.motorex.com](http://www.motorex.com)

**MOTOREX AG LANGENTHAL**  
 Industrie-Schmiertechnik  
 Postfach, CH-4901 Langenthal, Schweiz  
 Tel. +41 (0)62 919 74 74, Fax +41 (0)62 919 75 96  
[www.motorex.com](http://www.motorex.com)