



# UNISYNT VT

## SAE 75W/80

Fully synthetic transmission oil for heavy-duty trucks.

### Description

MOTOREX GEAR OIL UNISYNT VT SAE 75W/80 is a fully synthetic high-performance transmission oil for heavy-duty utility vehicles. The fully synthetic base fluids guarantee optimal low-temperature characteristics as well as excellent comfort when changing gear. MOTOREX GEAR OIL UNISYNT VT SAE 75W/80 is especially well suited for extended service intervals.

### Advantages

- fully synthetic, high-performance transmission oil
- reliable reserve capacity under extreme conditions
- dependable wear protection
- high oxidation stability and shear stability
- excellent low-temperature characteristics

### Field of application

MOTOREX GEAR OIL UNISYNT VT SAE 75W/80 is especially well suited for truck transmissions subject to heavy loads.

Be sure to observe the manufacturer's instructions.

### Specifications

MB APPROVAL 235.29  
 MAN 341 Typ E4/VR  
 VOLVO TRANSMISSION Oil 97307  
 VOITH RETARDER 153.00455710 Class C

### Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 306	<b>75W/80</b>
Colour		DIN ISO 2049	light red
Density at 20 °C	g/ml	ASTM D 4052	0.861
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	65
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	10.3
Viscosity index		DIN ISO 2909	144
Pourpoint	°C	ASTM D 5950	<-52
Flash point	°C	DIN EN ISO 2592	> 220

Water hazard class: WGK 2  
 Disposal code: EWC 130 206

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available for the product described.



**BUCHER AG LANGENTHAL**  
 MOTOREX-Schmiertechnik  
 Postfach, CH-4901 Langenthal, Switzerland  
 Tel. +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95  
[www.motorex.com](http://www.motorex.com)