

# XPERIENCE FS-X

## SAE 10W/60

Fully synthetic, high-performance motor oil

### Description

MOTOREX XPERIENCE FS-X SAE 10W/60 is a fully synthetic, high-performance motor oil developed for racing. The high-performance formula builds a lubricating film which is extremely resistant to pressure and, thanks to quick lubrication, guarantees excellent lubrication reliability and service life, as well as outstanding wear protection, even on cold engines.

### Advantages

- excellent wear protection
- performance-optimised
- excellent pressure stability
- quick lubrication time
- reduced oil consumption
- designed for racing
- suitable for CNG, LPG and hybrid vehicles

### Field of application

MOTOREX XPERIENCE FS-X SAE 10W/60 is designed for motorsports and is successfully used by major racing teams. Specially formulated and tested for petrol and diesel engines subject to high stress. Meets the strict requirements of Alfa Romeo, BMW and Porsche.

### Notes

MOTOREX XPERIENCE FS-X SAE 10W/60 can be mixed with all conventional motor oils of the same performance level. Oil and filters must be replaced in accordance with the manufacturer's specifications.

### Specifications

ACEA A3/B4-16; API SL; API SM; API SN

Safety + Performance

BMW Longlife-01; FIAT 9.55535-H3; MB 229.5; PORSCHE A40; RENAULT RN0700; RENAULT RN0710; VW 502 00; VW 505 00

### Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.852
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	162.9
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	23.1
Viscosity index		DIN ISO 2909	171
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-39
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-25 / 6051
Sulphate residue content	%	DIN EN ISO 6245	1.1
NOACK	%	CEC L-40-A-93	5
TBN	mg KOH/g	DIN ISO 3771	10.1

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

